



Retail
Hospitality
Healthcare
Architectural Lighting
Signage
Casino Design
Residential

eoslight.com



LUMINAIRE PHOTOMETRIC TEST REPORT

AURA LUMINAIRE RGB + 4000K-12 x 12-SP-4SL_IESNA95

NAME: EOS-AURA-4000k-12 x 12-SP-4SL	TYPE: EOS Aura Luminaire	WEIGHT: 1000G
SPEC.:	DIM.:	SERIAL No.:EOS
MFR.: EOS	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 47.26 lm/W
MODEL		Imax(cd)	247.0	S/MH(C0/180)	1.26	
NOMINAL POWER(W)	15.2	LOR(%)	100.4	S/MH(C90/270)	1.33	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	727.93	η UP,DN(C0-180)	0.0,49.1	
NOMINAL FLUX(lm)	725.055	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.3	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	24.4	η down(%)	100.4	CIBSE SHR MAX	1.50	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 03-06-2019

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.293
Humidity: 65.0%
Test Distance: 9.180m [K=1.0000]
Remarks: DWY




Retail
Hospitality
Healthcare
Architectural Lighting
Signage
Casino Design
Residential

eoslight.com

AAI Figure

NAME: EOS-AURA-4000k-12 x 12-SP-4SL	TYPE: EOS Aura Luminaire	WEIGHT: 1000G
SPEC.:	DIM.:	SERIAL No.:EOS
MFR.:EOS	SUR.:	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 03-06-2019

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.293
Humidity: 65.0%
Test Distance: 9.180m [K=1.0000]
Remarks: DWY



γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.293
Humidity: 65.0%
Test Distance: 9.180m [K=1.0000]
Remarks: DWY





